

	Bobcat S510	Bobcat S530	Bobcat S550	Bobcat S570	Bobcat S590
<b>Engine</b>					
Horsepower	49 HP	49 HP	61 HP	61 HP	66 HP
<b>Performance</b>					
Rated Operating Capacity	1650 lbs	1850 lbs	1750 lbs	1950 lbs	2100 lbs
Tipping Load	3300 lbs	3700 lbs	3500 lbs	3900 lbs	4200 lbs
Operating Weight	5922 lbs	6207 Lbs	6265 lbs	6395 lbs	6735 lbs
Travel Speed	7.4 mph	7.4 mph	7.4 mph	7.4 mph	7.4 mph
Travel Speed (2-speed option)	11.0 mph	11.0 mph	11.0 mph	11.0 mph	11.0 mph
<b>Hydraulic System</b>					
Auxiliary Std Flow	17.1 GPM	17.1 GPM	17.1 GPM	17.1 GPM	17.1 GPM
Auxiliary High Flow Option	NA	NA	26.7 GPM	26.7 GPM	26.7 GPM
<b>Dimension</b>					
Length with Bucket	133.0 in.	133.0 in.	133.0 in.	133.0 in.	133.0 in.
Width with Bucket	68.0 in.	68.0 in.	68.0 in.	68.0 in.	68.0 in.
Height with Operator Cab	77.8 in	77.8 in	77.8 in	77.8 in	77.8 in
Height to Bucket Hinge Pin	114.5 in	119.0 in	114.5 in	119.0 in	119.0 in
Lift Path Type	Radius	Vertical	Radius	Vertical	Vertical
<b>Factory Options</b>					
Roller Suspension	No	No	No	No	No
Selectable Joystick Controls	Yes	Yes	Yes	Yes	Yes

	Bobcat T550	Bobcat T590
<b>Engine</b>		
Horsepower	66 HP	66 HP
<b>Performance</b>		
Rated Operating Capacity (35% Of Tip)	1995 lbs	2100 lbs
Operating Capacity (50% of Tip)	2850 lbs	3000 lbs
Tipping Load	5700 lbs	6000 lbs
Operating Weight	7662 lbs	7870 lbs
Travel Speed	7.3 mph	7.3 mph
Travel Speed (2-speed option)	NA	NA
<b>Hydraulic System</b>		
Auxiliary Std Flow	17.1 GPM	17.1 GPM
Auxiliary High Flow	26.7 GPM	26.7 GPM
<b>Dimension</b>		
Length with Attachment	133.0 in	133.0 in
Width with Bucket	68.0 in	68.0 in
Height with Operator Cab	77.8 in	77.8 in
Height to Bucket Hinge Pin	114.5 in	119.0 in
Lift Path Type	Radius	Vertical
<b>Factory Options</b>		
Roller Suspension	Yes	Yes
Selectable Joystick Controls	Yes	Yes